



# SEPA Direct Debit Unpaid Report File Format

PAIN.002.001.03  
XML File Structure

This document is published by Bank of Ireland, and both it, and its' contents, are the property of Bank of Ireland.

This document may not be reproduced or further distributed, in whole or in part, without the express written permission of Bank of Ireland.

## Contents

1. Document Overview	3
2. Direct Debit Reconciliation	3
3. Document Purpose	4
4. Characteristics of PAIN.002.001.03	4
5. Field Types	4
6. Tag Depth Structure	4
7. Reason Codes	5
8. SEPA Direct Debit PAIN.002.001.03 Sample File	7
9. Change Control	36

# 1. Document Overview

This document details the PAIN.002.001.03 and Credit Settlement Report file formats that will be available to SEPA Direct Debit creditors (originators) where a SEPA r-message has been received against a payment.

A SEPA 'r-message' is rejection of a direct debit transaction. There are 2 types of r-messages, pre-settlement and post-settlement r-messages. The following describes the types of r-messages generated by debtor banks in SEPA:

- ▶ Pre-settlement r-messages include rejections (e.g. invalid IBAN) and refusals (e.g. debtor refuses the direct debit)
- ▶ Post settlement r-messages include returns (e.g. insufficient funds) and refunds (i.e. when the debtor requests refund of a direct debit.)

When you submit a file to Bank of Ireland, if there are errors when processing the direct debit transactions these rejections will be reported in the PAIN.002.001.03 file as pre and post settlement rejections.

The postings associated with these r-messages are group together based on certain criteria and posted to the creditors account as Bulk Debit entries. The Creditor Settlement Report details the individual transactions that are included in the bulk entry.

# 2. Direct Debit Reconciliation

## IRECC

Under IRECC, creditors are credited with the full value of the collection batch on settlement day. Bulk debits for any Unpaid returned are posted to the creditors account on settlement date + 2 (D+2).

For creditors who are registered for Unpaid information through ACREC, the unpaid bulks posted to the creditor's account are detailed to the creditors in the ACREC report. The current ACREC report details the breakdown of the bulk debits to the creditor's account and allows for both message and account reconciliation.

## SEPA

Under the SEPA scheme, creditors are credited with the full value of the collection batch, within a file, on settlement date. Bulk debits for any pre-settled r-messages are posted on settlement date of the collection batch, and any post settlement r-messages are posted at the end of the day of receipt. Post settlement r-messages can occur any day after the settlement date of the batch up to approximately 8 weeks after this date – this is to account for any refunds that occur during this period.

When a creditor previously used a single report (ACREC) for reconciliation they will now need to use two reports, the PAIN.002 for transaction reconciliation and the Creditor Settlement Report for account reconciliation.

1. PAIN.002.001.03: This is produced daily where an r-message has been received against the original PAIN.008.001.02 file. This report is available in two formats, an XML file and a reader friendly report, which can be used to automatically or manually reconcile direct debit transactions and represent direct debits where necessary.
2. Creditor Settlement Report: This is produced daily where posting has been applied to the creditor's account. This report is available in two formats, a .csv file and a reader friendly report that can be used to automatically, or manually, reconcile the creditor's account at the end of each day.

## 3. Document Purpose

The purpose of this document is to outline the:

1. PAIN.002.001.03 XML file format





Knowledge of XML is recommended to interpret this document.

## 4. Characteristics of PAIN.002.001.03

- 4.1. The PAIN.002.001.03 report will be available in XML and reader friendly HTML format.
- 4.2. The report will be available on Bank of Ireland's dedicated SEPA online channel, Business On Line Payments Plus. Bank of Ireland will communicate details of this channel and log on details to you.
- 4.3. R-messages (rejections, refusals, returns or refunds) received up to the end of the SEPA 8 week period following a direct debit will be provided on the PAIN.002.001.03.
- 4.4. The PAIN.002.001.03 file is generated per PAIN.008.001.02 file, per day. It details any r-messages that have been created against the PAIN.008.001.02 file and will contain the reason code for the rejection.
- 4.5. A PAIN.002.001.03 file will only be available if an r-message has been created for the associated PAIN.008.001.02 on a given day.
- 4.6. The r-messages contained in a PAIN.002.001.03 can be matched to the original transactions using the End to End ID.
- 4.7. PAIN.002.001.03 generated by Bank of Ireland will detail r-messages at transaction level. Bank of Ireland will not generate PAIN.002.001.03 messages for failures at file (Group Header) or batch (Payment Information) level. File failures will be reported as a specific message on the online channel.

## 5. Field Types

The following section details the type of fields that are contained in the specification document.

-  Usage Rules – Will always be adhered to
-  Always Present – Fields that will always be present on the PAIN.002.001.03 file
-  Optional Fields – This field will be populated if the corresponding optional field on the PAIN.008.001.02 was populated
-  Conditional Fields – This field will be populated if the corresponding conditional field on the PAIN.008.001.02 was populated

## 6. Tag Depth Structure

In the 'TAG DEPTH' column within the file format table below, each of the 'field name' tags are represented by a '+'.

These '+' icons represent the depth of the field name tag within the document.

For example:

'+' would represent a Parent Element

'++' would represent the Child Element of the previous Parent Element

Tag Depth	Tag Structure
+	<>
++	<> <>
+++	<> <> <>

## 7. Reason Codes

Creditors may receive the following reasons codes as part of the PAIN.002.001.03 message to detail the reason for the rejection. This code will be populated in the code tag, field index 3.23, as outlined in the Transaction Information block in the file format section of this document.

### Post-Settlement Returns/Refunds

Return codes

The following table lists the reason codes that could occur for a return message from a debtor bank:

ISO Code	SEPA Reason as specified in the Rulebook
AC01	Account identifier incorrect (i.e. invalid IBAN)
AC04	Account closed
AC06	Account blocked Account blocked for direct debit by the Debtor
AG01	Direct debit forbidden on this account for regulatory reasons
AG02	Operation/transaction code incorrect, invalid file format Usage Rule: To be used to indicate an incorrect 'operation/transaction' code
AM04	Insufficient funds
AM05	Duplicate collection
BE05	Identifier of the Creditor incorrect
MD01	No valid Mandate
MD07	Debtor deceased
MS02	Refusal by the Debtor
MS03	Reason not specified
RC01	Bank identifier incorrect (i.e. invalid BIC)
RR01	Missing Debtor Account or Identification
RR02	Missing Debtors Name or Address
RR03	Missing Creditors Name or Address
RR04	Regulatory Reason
SL01	Specific Service offered by the Debtor Bank

Refund Codes

The following table lists the reason codes that could occur for a refund message from a debtor bank

ISO Code	Tag Structure
MD01	Unauthorised transaction
MD06	Disputed authorised transaction

Note: MD01 may be used for both a Return and a Refund. To determine whether the transaction is a return or a refund:

- ▶ If it is a return, the Originator value in the Return Reason Information field will be populated with a BIC
- ▶ If it is a refund, the Originator value in the Return Reason Information field will be populated with a Debtor Name

## Pre-Settlement Rejects

The following table lists the reason codes that could occur for rejections or refusals from a debtor bank or rejections from Bank of Ireland:

ISO Code	SEPA Reason as specified in the Rulebook
AC01	Account identifier incorrect (i.e. invalid IBAN)
AC04	Account closed
AC06	Account blocked Account blocked for direct debit by the Debtor
AG01	Direct debit forbidden on this account for regulatory reasons
AG02	Operation/transaction code incorrect, invalid file format Usage Rule: To be used to indicate an incorrect 'operation/transaction' code
AM04	Insufficient funds
AM05	Duplicate collection
BE01	Debtor's name does not match with the account holder's name
BE05	Identifier of the Creditor Incorrect
FF01	Operation/transaction code incorrect, invalid file format Usage Rule: To be used to indicate an invalid file format.
MD01	No valid Mandate
MD02	Mandate data missing or incorrect
MD07	Debtor deceased
MS02	Refusal by the Debtor
MS03	Reason not specified
RC01	Bank identifier incorrect (i.e. invalid BIC)
RR01	Missing Debtor Account Or Identification
RR02	Missing Debtors Name Or Address
RR03	Missing Creditors Name Or Address
RR04	Regulatory Reason
SL01	Specific Service offered by the Debtor Bank
DNOR	Debtor bank is not registered under this BIC in the CSM

# 8. SEPA Direct Debit PAIN.002.001.03 Sample File

■ Usage Rules	■ Always Present
■ Optional Fileds	■ Conditional Fields

Field Index -Field Name – Tag (Field Index references EPC Implementation Guide)	Tag Depth	Content	Mandatory / Optional / Conditional	Populated By / From	Description / Value	Data
<?xml version="1.0" encoding="utf-8"?> <Document xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance" xmlns:xsd="http://www.w3.org/2001/XMLSchema" xmlns="urn:iso:std:iso:2002:tech:xsd:pain.002.001.03">			Always Present		Mandatory for all PAIN.002 XML files	
<CstmrPmtStsRpt>			Always Present		Mandatory for all PAIN.002 XML files	

Group Header – This will occur only once in the file						
Field Name – Tag (Field Index references EPC Implementation Guide)	Tag Depth	Content	Mandatory / Optional / Conditional	Populated By / From	Description / Value	Data
1.0 Group Header <GrpHdr>	+	Empty Tag	Always Present			
1.1 Messageldentification <MsgId>	++	Yes	Always Present	BOI	The reference of the bank/CSM initiating the 'R' message	<b>Data Type:</b> Text <b>Format:</b> Max length: 35 Min length: 1
1.2 Creation Date Time <CreDtTm>	++	Yes	Always Present	BOI	Date and time at which the message was created	<b>Data Type:</b> ISODatetime <b>Format:</b> YYYY-MM-DDTHH:MM:SS e.g. 2012-02-06T08:35:30
1.6 Creditor Agent <CdrAgt>	++	Empty Tag	Always Present			
1.6 Financial Institution Identification <FinInstnId>	+++	Empty Tag	Always Present			
1.6 BIC <BIC>	++++	Yes	Always Present	BOI	BOFIE2D	<b>Data Type:</b> BICIdentifier <b>Format:</b> [A-Z]{6,6}[A-Z2-9][A-NP-Z0-9]([A-Z0-9]{3,3}){0,1}

# 8. SEPA Direct Debit PAIN.002.001.03 Sample File

Usage Rules	Always Present
Optional Fileds	Conditional Fields

Original Group Information and Status							
Field Name – Tag (No. references EPC Implementation Guide)	Tag Level	Content	Mandatory / Optional / Conditional	Populated By / From	Description / Value	Data	
Original Group Information and Status will always be present and includes group header (file) level details from the submitted PAIN.008							
2.0	Original Group Information And Status <OrgnlGrpInfAndSts>	+	Empty Tag	Always Present			
2.1	Original Message Identification <OrgnlMsgId>	++	Yes	Always Present	PAIN.008	Point to point reference, as assigned by the original instructing party	<b>Data Type:</b> Text <b>Format:</b> Max length: 35 Min length: 1
2.2	Original Message Name Identification <OrgnlMsgNmId>	++	Yes	Always Present	Taken from file type that r-message is associated with.	Specifies the original message name identifier to which the message refers. i.e. PAIN.008.001.02	<b>Data Type:</b> Text <b>Format:</b> Max length: 35 Min length: 1
2.4	Original Number of Transactions <OrgnlNbOfTx>	++	Yes	Always Present	PAIN.008	Number of individual transactions contained in the original message.	<b>Data Type:</b> Numeric Text <b>Format:</b> [0-9]{1,15}
2.5	Original Control Sum <OrgnlCtrlSum>	++	Yes	Always Present	PAIN.008	Total of all individual amounts included in the original message	<b>Data Type:</b> Decimal Number <b>Format:</b> Fraction Digits: 2 Total Digits: 18
Original Payment Information and Status will be present for each Payment Information (batch) Block for which one or more transactions have been rejected and includes details from the submitted PAIN.008							
3.0	Original Payment Information And Status <OrgnlPmtInfAndSts>	+	Empty Tag	Always Present			
3.1	Original Payment Information Identification <OrgnlPmtInfId>	++	Yes	Always Present	PAIN.008	Unique identification, as assigned by the original sending party, to unambiguously identify the original payment information group	<b>Data Type:</b> Text <b>Format:</b> Max length: 35 Min length: 1



## 8. SEPA Direct Debit PAIN.002.001.03 Sample File

Usage Rules	Always Present
Optional Fields	Conditional Fields

Original Group Information and Status						
Field Name – Tag (No. references EPC Implementation Guide)	Tag Level	Content	Mandatory / Optional / Conditional	Populated By / From	Description / Value	Data
3.2 Original Number Of Transactions <OrgnNbOfTxs>	++	Yes	Always Present	PAIN.008	Number of individual transactions contained in the original payment information group	<b>Data Type:</b> Numeric Text <b>Format:</b> [0-9]{1,15}
3.3 Original Control Summ <OrgnCtrlSum>	++	Yes	Always Present	PAIN.008	Total of all individual amounts included in the original payment information group	

# 8. SEPA Direct Debit PAIN.002.001.03 Sample File

Usage Rules	Always Present
Optional Fileds	Conditional Fields

Transaction Information						
Field Name – Tag (No. references EPC Implementation Guide)	Tag Level	Content	Mandatory / Optional / Conditional	Populated By / From	Description / Value	Data
Transaction Information will always be present to detail the transaction which has failed, and will detail the original transaction level details from the submitted PAIN.008, as well as the r-message reason codes.						
3.15 Transaction Information And Status <TxInfAndSts>	++	Empty Tag	Always Present			
3.16 Status Identification <StsId>	+++	Yes	Always Present	Debtor Bank	Specific reference of the bank that initiated the reject	<b>Data Type:</b> Text <b>Format:</b> Max length: 35 Min length: 1
3.17 Original Instruction Identification <OrgnlInstrId>	+++	Yes	Populate if on PAIN.008	Field 2.30 from the PAIN.008	Unique identification, as assigned by the original instructing party for the original instructed party, to unambiguously identify the original instruction	<b>Data Type:</b> Text <b>Format:</b> Max length: 35 Min length: 1
3.18 Original End To End Identification <OrgnlEndToEndId>	+++	Yes	Always Present	Field 2.31 from the PAIN.008	Creditors reference of the Direct Debit Transaction	<b>Data Type:</b> Text <b>Format:</b> Max length: 35 Min length: 1
3.19 Transaction Status <TxSts>	+++	Yes	Always Present	Debtor Bank/ CSM	Will always be present with the code 'RJCT'	RJCT
3.20 Status Reason Information <StsRsnInf>	+++	Empty Tag	Always Present			
<b>Originator Usage Rule: Limited to BIC to identify the bank or CSM originating the status or 'Name' to indicate a CSM when it has no BIC</b>						
3.21 Originator <Orgtr>	++++	Empty Tag	See Originator Usage Rule			
3.21 Name <Nm>	+++++	Yes	See Originator Usage Rule	CSM or Debtor Name	'Name' to indicate a CSM or debtor if they have initiated the rejection	<b>Data Type:</b> Text <b>Format:</b> Max length: 70 Min length: 1
3.21 Identification <Id>	+++++	Empty Tag	See Originator Usage Rule			

# 8. SEPA Direct Debit PAIN.002.001.03 Sample File

Usage Rules	Always Present
Optional Fields	Conditional Fields

Transaction Information						
Field Name – Tag (No. references EPC Implementation Guide)	Tag Level	Content	Mandatory / Optional / Conditional	Populated By / From	Description / Value	Data
3.21 Organisation Identification <OrgId>	+++++	Empty Tag	See Originator Usage Rule			
3.21 BIC Or BEI <BICOrBEI>	+++++	Yes	See Originator Usage Rule	Creditor Bank / CSM / BOI	BIC to identify the bank or CSM originating the status	<b>Data Type:</b> AnyBICIdentifier <b>Format:</b> [A-Z]{6,6}[A-Z2-9][A-NP-Z0-9]([A-Z0-9]{3,3}){0,1}
3.22 Reason <Rsn>	++++	Empty Tag	See Originator Usage Rule			
3.23 Code <Cd>	++++	Yes	See Originator Usage Rule	Creditor Bank / CSM / BOI	See reason codes	See appendix for reason codes
<b>Original Transaction Reference Usage Rule: The message elements under 'Original Transaction Reference' will be populated with the same value as the message elements of the original instruction, as defined within the following elements.</b>						
3.32 Original Transaction Reference <OrgnTxRef>	+++	Empty Tag	Always Present			
3.34 Amount <Amt>	++++	Empty Tag	Always Present			
3.35 Instructed Amount <InstdAmt>	+++++	Yes	Always Present	PAIN.008	Amount of the Collection in Euro	AT-06 Amount of the Collection in Euro). Usage Rule: Only 'EUR' is allowed. Usage Rule: Amount must be 0.01 or more and 999999999.99 or less. Format Rule: The fractional part has a maximum of two digits

# 8. SEPA Direct Debit PAIN.002.001.03 Sample File

Usage Rules	Always Present
Optional Fields	Conditional Fields

Transaction Information						
Field Name – Tag (No. references EPC Implementation Guide)	Tag Level	Content	Mandatory / Optional / Conditional	Populated By / From	Description / Value	Data
3.40 Requested Collection Date <ReqdColltnDt>	++++	Yes	Always Present	Pain.008	Date and time at which the Creditor requests the instructed amount is collected from the debtor.	
3.42 Creditor Scheme Identification <CdtrSchmeld>	++++	Empty Tag	Always Present			
3.42 Identification <Id>	+++++	+++++	Always Present			
3.42 Private Identification <PrvtId>	+++++	Empty Tag	Always Present			
3.42 Other <Othr>	+++++	Empty Tag	Always Present			
3.42 Identification <Id>	+++++	Yes	Always Present	PAIN.008	This contains the Creditor Scheme(CID) - formerly OIN	<b>Data Type:</b> Text <b>Format:</b> Max length: 35 Min length: 1
3.42 Scheme Name <SchmeNm>	+++++	Empty Tag	Always Present			
3.42 Proprietary <Prtry>	+++++	Yes	Always Present	Pain.008	Name of the identification scheme, in a free text format.	Must contain 'SEPA'
3.55 Payment Type Information <PmtTpInf>	++++	Empty Tag	Always Present			
3.58 Service Level <SvcLvl>	+++++	Empty Tag	Always Present			
3.59 Code <Cd>	+++++	Yes	Always Present	PAIN.008		Must contain 'SEPA'
3.61 Local Instrument <LclInstrm>	+++++	Empty Tag	Always Present			
3.62 Code <Cd>	+++++	Yes	Always Present	Only CORE allowed PAIN.008		
3.64 SequenceType <SeqTp>	+++++	Yes	Always Present		Identifies the direct debit sequence, such as first, recurrent, final or one-off	<b>Code:</b> FRST, RCUR, OOFF, FNAL

## 8. SEPA Direct Debit PAIN.002.001.03 Sample File

Usage Rules	Always Present
Optional Fileds	Conditional Fields

Transaction Information						
Field Name – Tag (No. references EPC Implementation Guide)	Tag Level	Content	Mandatory / Optional / Conditional	Populated By / From	Description / Value	Data
3.65 Category Purpose <CtgyPurp>	+++++	Empty Tag	Populate if on PAIN.008			
3.66 Code <Cd>	+++++	Yes	Populate if on PAIN.008	PAIN.008	Category purpose in code form	<b>Format:</b> Max length: 4 Min length: 1 see code list on page11
3.67 Proprietary <Prtry>	+++++	Yes	Populate if on PAIN.008	PAIN.008	Category purpose in code form	<b>Data Type:</b> Text <b>Format:</b> Max length: 35 Min length: 1
3.69 Mandate Related Information <MndtRltdInf>	++++	Empty Tag	Always Present			
3.70 Mandate Identification <MndtId>	+++++	Yes	Always Present	PAIN.008	UMR from PAIN.008	<b>Data Type:</b> Text <b>Format:</b> Max length: 35 Min length: 1
3.71 Date of Signature <DtOfSgntr>	+++++	Yes	Always Present	PAIN.008	Date of Signing from PAIN.008	<b>Data Type:</b> ISO Date <b>Format:</b> YYYY-MM-DD e.g. 1998-03-30
3.72 Amendment Indicator <AmdmntInd>	+++++	Yes	Populate if on PAIN.008	PAIN.008	Indicator if an amendment has been made to amendment	True when an amendment has been made: otherwise nothing present
3.73 Amendment Information Details <AmdmntInfDtls>	+++++	Empty Tag	Populate if on PAIN.008			
3.74 Original Mandate Identification <OrgnlMndtId>	+++++	Yes	Populate if on PAIN.008	PAIN.008	Previous UMR is included here if an amendment has been made to the UMR	<b>Data Type:</b> Text <b>Format:</b> Max length: 35 Min length: 1
3.75 Original Creditor Scheme ID <OrgnlCdtrSchmeld>	+++++	Empty Tag	Populate if on PAIN.008			

# 8. SEPA Direct Debit PAIN.002.001.03 Sample File

Usage Rules	Always Present
Optional Fields	Conditional Fields

Transaction Information						
Field Name – Tag (No. references EPC Implementation Guide)	Tag Level	Content	Mandatory / Optional / Conditional	Populated By / From	Description / Value	Data
3.75 Name <Nm>	+++++++	Yes	Populate if on PAIN.008	PAIN.008	Previous creditor name. If present the new 'Name' must be specified under Creditor	<b>Data Type:</b> Text <b>Format:</b> Max length: 70 Min length: 1
3.75 Identification <Id>	+++++++	Empty Tag	Populate if on PAIN.008			
3.75 Private Identification <PrvtId>	+++++++	Empty Tag	Populate if on PAIN.008			
3.75 Other <Othr>	+++++++	Empty Tag	Populate if on PAIN.008			
3.75 Identification <Id>	+++++++ +++	Yes	Populate if on PAIN.008	PAIN.008	Previous creditor scheme identification	<b>Data Type:</b> Text <b>Format:</b> Max length: 35 Min length: 1
3.75 Scheme Name <SchmeNm>	+++++++ +++	Empty Tag	Populate if on PAIN.008			
3.75 Proprietary <Prtry>	+++++++ ++++	Yes	Populate if on PAIN.008	PAIN.008	Name of the identification scheme, in a free text form	Must contain SEPA
3.79 Original Debtor Account <OrgnIDbtrAcct>	+++++++	Empty Tag	Populate if on PAIN.008			
3.79 Identification <Id>	+++++++	Empty Tag	Populate if on PAIN.008			
3.79 IBAN <IBAN>	+++++++ ++	Yes	Populate if on PAIN.008	PAIN.008	Original debtor account that has been modified	<b>Data Type:</b> IBAN2007Identifier <b>Format:</b> [A-Z]{2,2}[0-9]{2,2}[a-zA-Z0-9]{1,30}
3.79 Other <Othr>	+++++++ ++	Empty Tag	Populate if on PAIN.008			

## 8. SEPA Direct Debit PAIN.002.001.03 Sample File

Usage Rules	Always Present
Optional Fileds	Conditional Fields

Transaction Information						
Field Name – Tag (No. references EPC Implementation Guide)	Tag Level	Content	Mandatory / Optional / Conditional	Populated By / From	Description / Value	Data
3.79 Identification <Id>	+++++++ +++	Yes	Populate if on PAIN.008	PAIN.008	Must be populated with 'SMNDA' to indicate same mandate with new debtor account	SMNDA
3.80 Original Debtor Agent <OrgnDbtrAgt>	+++++++	Empty Tag	Populate if on PAIN.008			
3.80 Financial Institution Identification <FinInstnId>	+++++++	Empty Tag	Populate if on PAIN.008			
3.80 BIC <BIC>	+++++++	Yes	Populate if on PAIN.008	PAIN.008		
3.88 Remittance Information <RmtInf>	++++	Empty Tag	Populate if on PAIN.008			
3.89 Unstructured <Ustrd>	+++++	Yes	Populate if on PAIN.008	PAIN.008	Free text provided for matching reconciliation	<b>Data Type:</b> Text <b>Format:</b> Max length: 140 Min length: 1
3.90 Structured <Strd>	+++++	Empty Tag	Populate if on PAIN.008			
3.110 Creditor Reference Information <CdtrRefInf>	+++++	Empty Tag	Populate if on PAIN.008			
3.111 Type <Tp>	+++++++	Empty Tag	Populate if on PAIN.008			
3.112 Code or Proprietary <CdOrPrtry>	+++++++	Empty Tag	Populate if on PAIN.008			
3.113 Code <Cd>	+++++++	Yes	Populate if on PAIN.008	PAIN.008	Type of creditor reference, in a coded form	Usage Rule Only 'SCOR' is allowed

## 8. SEPA Direct Debit PAIN.002.001.03 Sample File

■ Usage Rules	■ Always Present
■ Optional Fields	■ Conditional Fields

Transaction Information						
Field Name – Tag (No. references EPC Implementation Guide)	Tag Level	Content	Mandatory / Optional / Conditional	Populated By / From	Description / Value	Data
3.115 Issuer <lssr>	+++++++	Yes	Populate if on PAIN.008	PAIN.008	Entity that assigns the credit reference type	<b>Data Type:</b> Text <b>Format:</b> Max length: 35 Min length: 1
3.116 Reference <Ref>	+++++++	Yes	Populate if on PAIN.008	PAIN.008	Unique reference, as assigned by the creditor, to unambiguously refer to the payment transaction	<b>Data Type:</b> Text <b>Format:</b> Max length: 35 Min length: 1
3.120 Ultimate Debtor <UltmtDbtr>	++++	Empty Tag	Populate if on PAIN.008			
3.120 Name <Nm>	+++++	Yes	Populate if on PAIN.008	PAIN.008	Ultimate debtor name	<b>Data Type:</b> Text <b>Format:</b> Max length: 70 Min length: 1
3.120 Identification <Id>	+++++	Empty Tag	Populate if on PAIN.008			
3.120 Organisation Identification <OrgId>	+++++	Empty Tag	Populate if on PAIN.008			
3.120 BIC Or BEI <BICOrBEI>	+++++++	Yes	Populate if on PAIN.008	PAIN.008	BIC Identifier	<b>Data Type:</b> AnyBICIdentifier <b>Format:</b> [A-Z]{6,6}[A-Z2-9][A-NP-Z0-9]([A-Z0-9]{3,3}){0,1}
3.120 Other <Othr>	+++++++	Empty Tag	Populate if on PAIN.008			
3.120 Identification <Id>	+++++++	Yes	Populate if on PAIN.008	PAIN.008	Identification assigned by an institution	<b>Data Type:</b> Text <b>Format:</b> Max length: 35 Min length: 1
3.120 Scheme Name <SchmeNm>	+++++++	No	Populate if on PAIN.008			



## 8. SEPA Direct Debit PAIN.002.001.03 Sample File

■ Usage Rules	■ Always Present
■ Optional Fileds	■ Conditional Fields

Transaction Information						
Field Name – Tag (No. references EPC Implementation Guide)	Tag Level	Content	Mandatory / Optional / Conditional	Populated By / From	Description / Value	Data
3.120 Code <Cd>	+++++++	Yes	Populate if on PAIN.008	PAIN.008	Name of the identification scheme, in a coded form as published in an external list	<b>Data Type:</b> ExternalOrganisationIdentification1Code <b>Format:</b> Max length: 4 Min length: 1
3.120 Proprietary <Prtry>	+++++++	Yes	Populate if on PAIN.008	PAIN.008	Name of the identification scheme, in a free text form	<b>Data Type:</b> Text <b>Format:</b> Max length: 35 Min length: 1
3.120 Issuer <Issr>	+++++++	Yes	Populate if on PAIN.008	PAIN.008	Entity that assigns the identification	<b>Data Type:</b> Text <b>Format:</b> Max length: 35 Min length: 1
3.120 Private Identification <PrvtId>	+++++	Empty Tag	Populate if on PAIN.008			
3.120 Date And Place Of Birth <DtAndPlcOfBirth>	+++++	Empty Tag	Populate if on PAIN.008			
3.120 Birth Date <BirthDt>	+++++++	Yes	Populate if on PAIN.008	PAIN.008	Date on which a person is born	<b>Data Type:</b> ISODate <b>Format:</b> YYYY-MM-DD e.g. 1998-03-30
3.120 Province Of Birth <PrvcOfBirth>	+++++++	Yes	Populate if on PAIN.008	PAIN.008	Province where a person was born	<b>Data Type:</b> Text <b>Format:</b> Max length: 35 Min length: 1
3.120 City Of Birth <CityOfBirth>	+++++++	Yes	Populate if on PAIN.008	PAIN.008	City where a person was born	<b>Data Type:</b> Text <b>Format:</b> Max length: 35 Min length: 1
3.120 Country Of Birth <CtryOfBirth>	+++++++	Yes	Populate if on PAIN.008	PAIN.008	Country where a person was born	<b>Data Type:</b> CountryCode <b>Format:</b> [A-Z]{2,2}

## 8. SEPA Direct Debit PAIN.002.001.03 Sample File

Usage Rules	Always Present
Optional Fields	Conditional Fields

Transaction Information						
Field Name – Tag (No. references EPC Implementation Guide)	Tag Level	Content	Mandatory / Optional / Conditional	Populated By / From	Description / Value	Data
3.120 Other <Othr>	+++++++	Empty Tag	Populate if on PAIN.008	PAIN.008		
3.120 Identification <Id>	+++++++	Yes	Populate if on PAIN.008	PAIN.008	Identification assigned by an institution	<b>Data Type:</b> Text <b>Format:</b> Max length: 35 Min length: 1
3.120 Scheme Name <SchmeNm>	+++++++	Empty Tag	Populate if on PAIN.008			
3.120 Code <Cd>	+++++++	Yes	Populate if on PAIN.008	PAIN.008	Name of the identification scheme, in a coded form as published in an external list	<b>Data Type:</b> ExternalPersonal Identification1Code <b>Format:</b> Max length: 4 Min length: 1
3.120 Proprietary <Prtry>	+++++++	Yes	Populate if on PAIN.008	PAIN.008	Name of the identification scheme, in a free text form	<b>Data Type:</b> Text <b>Format:</b> Max length: 35 Min length: 1
3.120 Issuer <Issr>	+++++++	Yes	Populate if on PAIN.008	PAIN.008	Entity that assigns the identification	<b>Data Type:</b> Text <b>Format:</b> Max length: 35 Min length: 1
3.121 Debtor <Dbtr>	++++	Empty Tag	Always Present			
3.121 Name <Nm>	++++	Yes	Always Present	PAIN.008	Debtor name	<b>Data Type:</b> Text <b>Format:</b> Max length: 70 Min length: 1
3.121 Postal Address <PstlAdr>	++++	Empty Tag	Populate if on PAIN.008			
3.121 Country <Ctry>	++++	Yes	Populate if on PAIN.008	PAIN.008	Country code	<b>Data Type:</b> CountryCode <b>Format:</b> [A-Z]{2} SO 3166, Alpha-2 code

## 8. SEPA Direct Debit PAIN.002.001.03 Sample File

Usage Rules	Always Present
Optional Fields	Conditional Fields

Transaction Information						
Field Name – Tag (No. references EPC Implementation Guide)	Tag Level	Content	Mandatory / Optional / Conditional	Populated By / From	Description / Value	Data
3.121 Address Line <AdrLine> (2)	++++++	Yes	Populate if on PAIN.008	PAIN.008	Debtor address in free format text. Note: Two occurrences of this tag are allowed	<b>Data Type:</b> Text <b>Format:</b> Max length: 70 Min length: 1
3.121 Identification <Id>	+++++	Empty Tag	Populate if on PAIN.008			
3.121 Organisation Identification <OrgId>	++++++	Empty Tag	Populate if on PAIN.008			
3.121 BIC Or BEI <BICOrBEI>	+++++++	Yes	Populate if on PAIN.008	PAIN.008	BIC Identifier	<b>Data Type:</b> AnyBICIdentifier <b>Format:</b> [A-Z]{6,6}[A-Z2-9][A-NP-Z0-9]{3,3}{0,1}
3.121 Other <Othr>	+++++++	Empty Tag	Populate if on PAIN.008			
3.121 Identification <Id>	+++++++	Yes	Populate if on PAIN.008	PAIN.008	Identification assigned by an institution	<b>Data Type:</b> Text <b>Format:</b> Max length: 35 Min length: 1
3.121 Scheme Name <SchmeNm>	+++++++	No	Populate if on PAIN.008			
3.121 Code <Cd>	+++++++	Yes	Populate if on PAIN.008	PAIN.008	Name of the identification scheme, in a coded form as published in an external list	<b>Data Type:</b> ExternalOrganisationIdentification1Code <b>Format:</b> Max length: 4 Min length: 1
3.121 Proprietary <Prtry>	+++++++	Yes	Populate if on PAIN.008	PAIN.008	Name of the identification scheme, in a free text form	<b>Data Type:</b> Text <b>Format:</b> Max length: 35 Min length: 1

## 8. SEPA Direct Debit PAIN.002.001.03 Sample File

Usage Rules	Always Present
Optional Fields	Conditional Fields

Transaction Information						
Field Name – Tag (No. references EPC Implementation Guide)	Tag Level	Content	Mandatory / Optional / Conditional	Populated By / From	Description / Value	Data
3.121 Issuer <Issr>	+++++++	Yes	Populate if on PAIN.008	PAIN.008	Entity that assigns the identification	<b>Data Type:</b> Text <b>Format:</b> Max length: 35 Min length: 1
3.121 Private Identification <PrvtId>	+++++	Empty Tag	Populate if on PAIN.008			
3.121 Date And Place Of Birth <DtAndPlcOfBirth>	+++++	Empty Tag	Populate if on PAIN.008			
3.121 Birth Date <BirthDt>	+++++++	Yes	Populate if on PAIN.008	PAIN.008	Date on which a person is born	<b>Data Type:</b> ISODate <b>Format:</b> YYYY-MM-DD e.g. 1998-03-30
3.121 Province Of Birth <PrvcOfBirth>	+++++++	Yes	Populate if on PAIN.008	PAIN.008	Province where a person was born	<b>Data Type:</b> Text <b>Format:</b> Max length: 35 Min length: 1
3.121 City Of Birth <CityOfBirth>	+++++++	Yes	Populate if on PAIN.008	PAIN.008	City where a person was born	<b>Data Type:</b> Text <b>Format:</b> Max length: 35 Min length: 1
3.121 Country Of Birth <CtryOfBirth>	+++++++	Yes	Populate if on PAIN.008	PAIN.008	Country where a person was born	<b>Data Type:</b> CountryCode <b>Format:</b> [A-Z]{2,2}
3.121 Other <Othr>	+++++	Empty Tag	Populate if on PAIN.008			
3.121 Identification <Id>	+++++++	Yes	Populate if on PAIN.008	PAIN.008	Identification assigned by an institution	<b>Data Type:</b> Text <b>Format:</b> Max length: 35 Min length: 1
3.121 Scheme Name <SchmeNm>	+++++++	Empty Tag	Populate if on PAIN.008			

# 8. SEPA Direct Debit PAIN.002.001.03 Sample File

Usage Rules	Always Present
Optional Fields	Conditional Fields

Transaction Information						
Field Name – Tag (No. references EPC Implementation Guide)	Tag Level	Content	Mandatory / Optional / Conditional	Populated By / From	Description / Value	Data
3.121 Code <Cd>	+++++++	Yes	Populate if on PAIN.008	PAIN.008	Name of the identification scheme, in a coded form as published in an external list	<b>Data Type:</b> ExternalPersonalIdentification1Code <b>Format:</b> Max length: 4 Min length: 1
3.121 Proprietary <Prtry>	+++++++	Yes	Populate if on PAIN.008	PAIN.008	Name of the identification scheme, in a free text form	<b>Data Type:</b> Text <b>Format:</b> Max length: 35 Min length: 1
3.121 Issuer <Issr>	+++++++	Yes	Populate if on PAIN.008	PAIN.008	Entity that assigns the identification	<b>Data Type:</b> Text <b>Format:</b> Max length: 35 Min length: 1
3.122 Debtor Account <DbtrAcct>	++++	Empty Tag	Always Present			
3.122 Identification <Id>	++++	Empty Tag	Always Present			
3.122 IBAN <IBAN>	+++++	Yes	Always Present	PAIN.008	International Bank Account Number (IBAN)	<b>Data Type:</b> IBAN2007Identifier <b>Format:</b> [A-Z]{2,2}[0-9]{2,2}[a-zA-Z0-9]{1,30}
<b>Debtor Agent. Usage Rule: Will not be present if the Debtor BIC is not provided in the pain.008 and has not been derived from the Debtor IBAN provided.</b>						
3.123 Debtor Agent <DbtrAgt>	++++	Empty Tag	Optional	See Usage Rule		
3.123 Financial Institution Identification <FinInstnId>	+++++	Empty Tag	Optional	See Usage Rule		
3.123 BIC <BIC>	+++++	Yes	Optional	See Usage Rule	Bank Identifier Code Will be present if provided on the pain.008 or has been successfully derived from the Debtor IBAN.	<b>Data Type:</b> BICIdentifier <b>Format:</b> [A-Z]{6,6}[A-Z2-9][A-NP-Z0-9]([A-Z0-9]{3,3}){0,1}

## 8. SEPA Direct Debit PAIN.002.001.03 Sample File

Usage Rules	Always Present
Optional Fields	Conditional Fields

Transaction Information						
Field Name – Tag (No. references EPC Implementation Guide)	Tag Level	Content	Mandatory / Optional / Conditional	Populated By / From	Description / Value	Data
3.125 Creditor Agent <CdtrAgt>	++++	Empty Tag	Always Present			
3.125 Financial Institution Identification <FinInstnId>	+++++	Empty Tag	Always Present			
3.125 BIC <BIC>	+++++	Yes	Always Present	PAIN.008	Bank Identifier Code	<b>Data Type:</b> BICIdentifier <b>Format:</b> [A-Z]{6,6}[A-Z2-9][A-NP-Z0-9]([A-Z0-9]{3,3}){0,1}
3.127 Creditor <Cdtr>	++++	Empty Tag	Always Present			
3.127 Name <Nm>	+++++	Yes	Always Present	PAIN.008	Name by which a party is known and which is usually used to identify that party	<b>Data Type:</b> Text <b>Format:</b> Max length: 70 Min length: 1
3.127 Postal Address <PstlAdr>	+++++	Empty Tag	Populate if on PAIN.008			
3.127 Country <Ctry>	+++++	Yes	Populate if on PAIN.008	PAIN.008	Country Code	<b>Format:</b> [A-Z]{2,2} ISO 3166, Alpha-2 Code
3.127 Address Line <AdrLine> (2)	+++++	Yes	Populate if on PAIN.008	PAIN.008	Postal address in free format text. Note: Two occurrences of this tag are allowed	<b>Data Type:</b> Text <b>Format:</b> Max length: 70 Min length: 1
3.128 Creditor Account <CdtrAcct>	++++	Empty Tag	Always Present			
3.128 Identification <Id>	+++++	Empty Tag	Always Present			
3.128 IBAN <IBAN>	+++++	Yes	Always Present	PAIN.008	International Bank Account Number (IBAN)	<b>Data Type:</b> IBAN2007Identifier <b>Format:</b> [A-Z]{2,2}[0-9]{2,2}[a-zA-Z0-9]{1,30}

## 8. SEPA Direct Debit PAIN.002.001.03 Sample File

■ Usage Rules	■ Always Present
■ Optional Fileds	■ Conditional Fields

Transaction Information						
Field Name – Tag (No. references EPC Implementation Guide)	Tag Level	Content	Mandatory / Optional / Conditional	Populated By / From	Description / Value	Data
3.128 Currency <Ccy>	++++	Yes	Populate if on PAIN.008	PAIN.008	Identification of the currency in which the account is held Note: No processing or validation is completed on this field – for information purpose only	Currency Code <b>Format:</b> [A-Z]{3,3} Valid active or historic currency codes are registered with the ISO 4217
3.129 Ultimate Creditor <UltmtCdtr>	++++	Empty Tag	Populate if on PAIN.008			
3.129 Name <Nm>	+++++	Yes	Populate if on PAIN.008	PAIN.008	Ultimate party to which an amount of money is due	<b>Data Type:</b> Text <b>Format:</b> Max length: 70 Min length: 1
3.129 Identification <Id>	+++++	Empty Tag	Populate if on PAIN.008			
3.129 Organisation Identification <OrgId>	+++++	Empty Tag	Populate if on PAIN.008			
3.129 BIC Or BEI <BICOrBEI>	+++++++	Yes	Populate if on PAIN.008	PAIN.008	BIC Identifier	<b>Data Type:</b> AnyBICIdentifier <b>Format:</b> [A-Z]{6,6}[A-Z2-9][A-NP-Z0-9]([A-Z0-9]{3,3}){0,1}
3.129 Other <Othr>	+++++++	Empty Tag	Populate if on PAIN.008			
3.129 Identification <Id>	+++++++	Yes	Populate if on PAIN.008	PAIN.008		
3.129 Scheme Name <SchmeNm>	+++++++	Empty Tag	Populate if on PAIN.008			

## 8. SEPA Direct Debit PAIN.002.001.03 Sample File

<span style="display: inline-block; width: 10px; height: 10px; background-color: black; margin-right: 5px;"></span> Usage Rules	<span style="display: inline-block; width: 10px; height: 10px; background-color: lightblue; margin-right: 5px;"></span> Always Present
<span style="display: inline-block; width: 10px; height: 10px; background-color: lightgreen; margin-right: 5px;"></span> Optional Fileds	<span style="display: inline-block; width: 10px; height: 10px; background-color: orange; margin-right: 5px;"></span> Conditional Fields

Transaction Information						
Field Name – Tag (No. references EPC Implementation Guide)	Tag Level	Content	Mandatory / Optional / Conditional	Populated By / From	Description / Value	Data
3.129 Code <Cd>	+++++++	Yes	Populate if on PAIN.008	PAIN.008	Name of the identification scheme, in a coded form as published in an external list	<b>Data Type:</b> ExternalOrganisationIdentification1Code <b>Format:</b> Max length: 4 Min length: 1
3.129 Proprietary <Prtry>	+++++++	Yes	Populate if on PAIN.008	PAIN.008	Name of the identification scheme, in a free text form	<b>Data Type:</b> Text <b>Format:</b> Max length: 35 Min length: 1
3.129 Issuer <Issr>	+++++++		Populate if on PAIN.008	PAIN.008	Entity that assigns the identification	<b>Data Type:</b> Text <b>Format:</b> Max length: 35 Min length: 1
3.129 Private Identification <PrvtId>	+++++	Empty Tag	Populate if on PAIN.008			
3.129 Date And Place Of Birth <DtAndPlcOfBirth>	+++++	Empty Tag	Populate if on PAIN.008			
3.129 Birth Date <BirthDt>	+++++++	Yes	Populate if on PAIN.008	PAIN.008	Date on which a person is born	<b>Data Type:</b> ISODate <b>Format:</b> YYYY-MM-DD e.g. 1998-03-30
3.129 Province Of Birth <PrvcOfBirth>	+++++++	Yes	Populate if on PAIN.008	PAIN.008	Province where a person was born	<b>Data Type:</b> Text <b>Format:</b> Max length: 35 Min length: 1
3.129 City Of Birth <CityOfBirth>	+++++++	Yes	Populate if on PAIN.008	PAIN.008	City where a person was born	<b>Data Type:</b> Text <b>Format:</b> Max length: 35 Min length: 1
3.129 Country Of Birth <CtryOfBirth>	+++++++	Yes	Populate if on PAIN.008	PAIN.008	Country where a person was born	<b>Data Type:</b> CountryCode <b>Format:</b> [A-Z]{2,2}



## 8. SEPA Direct Debit PAIN.002.001.03 Sample File

■ Usage Rules	■ Always Present
■ Optional Fields	■ Conditional Fields

Transaction Information						
Field Name – Tag (No. references EPC Implementation Guide)	Tag Level	Content	Mandatory / Optional / Conditional	Populated By / From	Description / Value	Data
3.129 Other <Othr>	+++++++	Empty Tag	Populate if on PAIN.008			
3.129 Identification <Id>	+++++++	Yes	Populate if on PAIN.008	PAIN.008	Identification assigned by an institution	<b>Data Type:</b> Text <b>Format:</b> Max length: 35 Min length: 1
3.129 Scheme Name <SchmeNm>	+++++++	Empty Tag	Populate if on PAIN.008			
3.129 Code <Cd>	+++++++	Yes	Populate if on PAIN.008	PAIN.008	Name of the identification scheme, in a coded form as published in an external list	<b>Data Type:</b> ExternalPersonal Identification1Code <b>Format:</b> Max length: 4 Min length: 1
3.129 Proprietary <Prtry>	+++++++	Yes	Populate if on PAIN.008	PAIN.008	Name of the identification scheme, in a free text form	<b>Data Type:</b> Text <b>Format:</b> Max length: 35 Min length: 1
3.129 Issuer <lssr>	+++++++	Yes	Populate if on PAIN.008	PAIN.008	Entity that assigns the identification	<b>Data Type:</b> Text <b>Format:</b> Max length: 35 Min length: 1

## 8. SEPA Direct Debit PAIN.002.001.03 Sample File

```
<?xml version="1.0" encoding="utf-8"?>
<!--
Following submission of the PAIN.008.001.02 collection file, four transactions have been rejected for various reasons detailed below.
These rejected transactions come from two separate batches within the original PAIN.008.001.02 file, batch PMTINFID1 and batch PMTINFID2
-->
<Document xmlns:xsi="http://www.w3.org/2001/XMLSchemainstance" xmlns:xsd="http://www.w3.org/2001/XMLSchema"
xmlns="urn:iso:std:iso:20022:tech:xsd:pain.002.001.03">
<CstmrPmtStsRpt>
<GrpHdr>
    <MsgId>MSGID99345678912</MsgId>
<!--
Message ID of the PAIN.002 message - assigned by the Creditor Bank to uniquely identify the PAIN.002 message
-->
    <CreDtTm>2013-10-08T20:49:00</CreDtTm>
        <CdtrAgt>
            <FinInstnId>
                <BIC>BOFIIE2D</BIC>
<!--
BIC of Financial Institution that created the message - always BOI BIC
-->
            </FinInstnId>
        </CdtrAgt>
</GrpHdr>
<OrgnlGrpInfAndSts>
    <OrgnlMsgId>MSGID12345678912</OrgnlMsgId>
<!--
Unique file identification of the corresponding PAIN.008.001.02 file as assigned by the creditor
-->
<!--
<OrgnlMsgNmId>PAIN.008.001.02</OrgnlMsgNmId>
<OrgnlNbOfTxes>4</OrgnlNbOfTxes>
<OrgnlCtrlSum>400.4</OrgnlCtrlSum>
</OrgnlGrpInfAndSts>
<OrgnlPmtInfAndSts>
<OrgnlPmtInfId>PMTINFID1</OrgnlPmtInfId>
Unique identification of batch in which two transactions have failed. The unique identifier is provided by the creditor in the corresponding
PAIN.008.001.02 file
-->
<!--
<OrgnlNbOfTxes>2</OrgnlNbOfTxes>
```

## 8. SEPA Direct Debit PAIN.002.001.03 Sample File

```
<OrgnlCtrlSum>200.2</OrgnlCtrlSum>
```

```
<TxInfAndSts>
```

The following transaction has been rejected due to invalid IBAN (AC01)- all transaction level fields from the original PAIN.008.001.02 message will be contained in the rejected transaction information

```
-->
```

```
<!--
```

```
<StsId>IDREJ1</StsId>
```

Reference of the bank that initiated the payment rejection

```
-->
```

```
<!--
```

```
<OrgnlEndToEndId>E2EID1</OrgnlEndToEndId>
```

Unique End to End identifier for the transaction as assigned by the creditor in the corresponding PAIN.008.001.02 message

```
-->
```

```
<TxSts>RJCT</TxSts>
```

```
<StsRsnInf>
```

```
<Orgtr>
```

```
<Id>
```

```
<OrgId>
```

```
<BICOrBEI>BOFIE2D</BICOrBEI>
```

```
</OrgId>
```

```
</Id>
```

```
</Orgtr>
```

```
<Rsn>
```

```
<Cd>AC01</Cd>
```

```
</Rsn>
```

```
</StsRsnInf>
```

```
<OrgnlTxRef>
```

```
<Amt><InstdAmt Ccy="EUR">100.1</InstdAmt></Amt>
```

```
<ReqdColltnDt>2013-10-09</ReqdColltnDt>
```

```
<CdtrSchmeId>
```

```
<Id>
```

```
<PrvtId>
```

```
<Othr>
```

```
<Id>IE97ZZZ123456</Id>
```

```
<SchmeNm>
```

```
<Prtry>SEPA</Prtry>
```

```
</SchmeNm>
```

```
</Othr>
```

```
</PrvtId>
```

## 8. SEPA Direct Debit PAIN.002.001.03 Sample File

```

        </Id>
    </CdtrSchmeId>
    <PmtTpInf>
    <SvcLvl>
        <Cd>SEPA</Cd>
    </SvcLvl>
    <LclInstrm>
        <Cd>CORE</Cd>
    </LclInstrm>
    <SeqTp>FRST</SeqTp>
    </PmtTpInf>
    <MndtRltdInf>
        <MndtId>MANDATEID1</MndtId>
        <DtOfSgntr>2013-09-01</DtOfSgntr>
    </MndtRltdInf>
    <Dbtr>
        <Nm>DEBTOR1</Nm>
    </Dbtr>
    <DbtrAcct>
        <Id>
            <IBAN>IE82BOFI90393929352659</IBAN>
        </Id>
    </DbtrAcct>
    <DbtrAgt>
        <FinInstnId>
            <BIC>BOFIE2D</BIC>
        </FinInstnId>
    </DbtrAgt>
    <CdtrAgt>
        <FinInstnId>
            <BIC>BOFIE2D</BIC>
        </FinInstnId>
    </CdtrAgt>
    <Cdtr>
        <Nm>CREDITOR</Nm>
    </Cdtr>
<!--
<CdtrAcct>
<Id>
<IBAN>IE75BOFI90377959996017</IBAN>
```

## 8. SEPA Direct Debit PAIN.002.001.03 Sample File

```
</Id>
<Ccy>EUR</Ccy>
</CdtrAcct>
</OrgnlTxRef>
</TxInfAndSts>
<TxInfAndSts>
The following transaction has been rejected due to a refusal by the debtor (MS03)
-->
```

```
    <StsId>IDREJ2</StsId>
    <OrgnlEndToEndId>E2EID2</OrgnlEndToEndId>
    <TxSts>RJCT</TxSts>
    <StsRsnInf>
      <Orgtr>
        <Nm>DEBTOR2</Nm>
      </Orgtr>
      <Rsn>
        <Cd>MS02</Cd>
      </Rsn>
    </StsRsnInf>
    <OrgnlTxRef>
      <Amt><InstdAmt Ccy="EUR">100.1</InstdAmt></Amt>
      <ReqdColltnDt>2013-10-09</ReqdColltnDt>
      <CdtrSchmeId>
        <Id>
          <PrvtId>
            <Othr>
              <Id>IE97ZZZ123456</Id>
              <SchmeNm>
                <Prtry>SEPA</Prtry>
              </SchmeNm>
            </Othr>
          </PrvtId>
        </Id>
      </CdtrSchmeId>
      <PmtTpInf>
        <SvcLvl>
          <Cd>SEPA</Cd>
        </SvcLvl>
        <LclInstrm>
          <Cd>CORE</Cd>
```

## 8. SEPA Direct Debit PAIN.002.001.03 Sample File

```

        </LclInstrm>
        <SeqTp>FRST</SeqTp>
    </PmtTpInf>
    <MndtRltdInf>
        <MndtId>MANDATEID2</MndtId>
        <DtOfSgntr>2013-09-01</DtOfSgntr>
        <AmdmntInd>true</AmdmntInd>
        <AmdmntInfDtls>
            <OrgnlDbtrAcct>
                <Id>
                    <Othr>
                        <Id>SMNDA</Id>
                    </Othr>
                </Id>
            </OrgnlDbtrAcct>
        </AmdmntInfDtls>
    </MndtRltdInf>
    <Dbtr>
        <Nm>DEBTOR2</Nm>
    </Dbtr>
    <DbtrAcct>
        <Id>
            <IBAN>IE19BOFI90529930903788</IBAN>
        </Id>
    </DbtrAcct>
    <DbtrAgt>
        <FinInstnId>
            <BIC>BOFIIE2D</BIC>
        </FinInstnId>
    </DbtrAgt>
    <CdtrAgt>
        <FinInstnId>
            <BIC>BOFIIE2D</BIC>
        </FinInstnId>
    </CdtrAgt>
    <Cdtr>
        <Nm>CREDITOR</Nm>
    </Cdtr>
<!--
<CdtrAcct>
```

## 8. SEPA Direct Debit PAIN.002.001.03 Sample File

```
<Id>
<IBAN>IE75BOFI90377959996017</IBAN>
</Id>
<Ccy>EUR</Ccy>
</CdtrAcct>
</OrgnlTxRef>
</TxInfAndSts>
</OrgnlPmtInfAndSts>
<OrgnlPmtInfAndSts>
Second batch from the original PAIN.008.001.02 which also has two rejected transactions
-->
<!--
<OrgnlPmtInfId>PMTINFID2</OrgnlPmtInfId>
<OrgnlNbOfTx>2</OrgnlNbOfTx>
<OrgnlCtrlSum>200.2</OrgnlCtrlSum>
<TxInfAndSts>
The following transaction has been rejected since the debtor requested a refund for an authorised transaction (MD06)
-->
    <StsId>IDREJ3</StsId>
    <OrgnlEndToEndId>E2EID3</OrgnlEndToEndId>
    <TxSts>RJCT</TxSts>
    <StsRsnInf>
        <Orgtr>
            <Nm>DEBTOR3</Nm>
        </Orgtr>
        <Rsn>
            <Cd>MD06</Cd>
        </Rsn>
    </StsRsnInf>
    <OrgnlTxRef>
        <Amt><InstdAmt Ccy="EUR">100.1</InstdAmt></Amt>
        <ReqdColltnDt>2013-10-09</ReqdColltnDt>
        <CdtrSchmeId>
            <Id>
                <PrvtId>
                    <Othr>
                        <Id>IE97ZZZ123456</Id>
                        <SchmeNm>
                            <Prtry>SEPA</Prtry>
                        </SchmeNm>
                    </Othr>
                </PrvtId>
            </Id>
        </CdtrSchmeId>
    </OrgnlTxRef>

```

## 8. SEPA Direct Debit PAIN.002.001.03 Sample File

```

                </Othr>
            </PrvtId>
        </Id>
    </CdtrSchmeId>
    <PmtTpInf>
        <SvcLvl>
            <Cd>SEPA</Cd>
        </SvcLvl>
        <LclInstrm>
            <Cd>CORE</Cd>
        </LclInstrm>
        <SeqTp>RCUR</SeqTp>
    </PmtTpInf>
    <MndtRltdInf>
        <MndtId>MANDATEID3</MndtId>
        <DtOfSgntr>2013-09-01</DtOfSgntr>
    </MndtRltdInf>
    <Dbtr>
        <Nm>DEBTOR3</Nm>
    </Dbtr>
    <DbtrAcct>
        <Id>
            <IBAN>IE11BOFI90570714221998</IBAN>
        </Id>
    </DbtrAcct>
    <DbtrAgt>
        <FinInstnId>
            <BIC>BOFIIE2D</BIC>
        </FinInstnId>
    </DbtrAgt>
    <CdtrAgt>
        <FinInstnId>
            <BIC>BOFIIE2D</BIC>
        </FinInstnId>
    </CdtrAgt>
    <Cdtr>
        <Nm>CREDITOR</Nm>
    </Cdtr>
    <CdtrAcct>

```

<!--



## 8. SEPA Direct Debit PAIN.002.001.03 Sample File

```
<Id>  
<IBAN>IE59BOFI90565164751321</IBAN>  
</Id>  
<Ccy>EUR</Ccy>  
</CdtrAcct>  
</OrgnlTxRef>  
</TxInfAndSts>  
<TxInfAndSts>
```

The following transaction is rejected since there was insufficient funds in the debtor account to fund the transaction (AM04)  
-->

```
<StsId>IDREJ4</StsId>  
<OrgnlEndToEndId>E2EID4</OrgnlEndToEndId>  
<TxSts>RJCT</TxSts>  
<StsRsnInf>  
  <Orgtr>  
    <Id>  
      <OrgId>  
        <BICOrBEI>BOFIE2D</BICOrBEI>  
      </OrgId>  
    </Id>  
  </Orgtr>  
  <Rsn>  
    <Cd>AM04</Cd>  
  </Rsn>  
</StsRsnInf>  
<OrgnlTxRef>  
  <Amt><InstdAmt Ccy="EUR">100.1</InstdAmt></Amt>  
  <ReqdColltnDt>2013-10-09</ReqdColltnDt>  
  <CdtrSchmeId>  
    <Id>  
      <PrvtId>  
        <Othr>  
          <Id>IE97ZZZ123456</Id>  
          <SchmeNm>  
            <Prtry>SEPA</Prtry>  
          </SchmeNm>  
        </Othr>  
      </PrvtId>  
    </Id>  
  </CdtrSchmeId>
```

## 8. SEPA Direct Debit PAIN.002.001.03 Sample File

```
<PmtTpInf>
  <SvcLvl>
    <Cd>SEPA</Cd>
  </SvcLvl>
  <LclInstrm>
    <Cd>CORE</Cd>
  </LclInstrm>
  <SeqTp>RCUR</SeqTp>
</PmtTpInf>
<MndtRltdInf>
  <MndtId>MANDATEID4</MndtId>
  <DtOfSgntr>2013-09-01</DtOfSgntr>
</MndtRltdInf>
<Dbtr>
  <Nm>DEBTOR4</Nm>
</Dbtr>
<DbtrAcct>
  <Id>
    <IBAN>IE22BOFI90573146641815</IBAN>
  </Id>
</DbtrAcct>
<DbtrAgt>
  <FinInstnId>
    <BIC>BOFIIE2D</BIC>
  </FinInstnId>
</DbtrAgt>
<CdtrAgt>
  <FinInstnId>
    <BIC>BOFIIE2D</BIC>
  </FinInstnId>
</CdtrAgt>
<Cdtr>
  <Nm>CREDITOR</Nm>
</Cdtr>
  <CdtrAcct>
    <Id>
      <IBAN>IE59BOFI90565164751321</IBAN>
    </Id>
    <Ccy>EUR</Ccy>
  </CdtrAcct>
```

## 8. SEPA Direct Debit PAIN.002.001.03 Sample File

```
                </OrgnlTxRef>
            </TxInfAndSts>
        </OrgnlPmtInfAndSts>
    </CstmrPmtStsRpt>
</Document>
```

## 9. Change Control

Version:	Date	Section	Comments
1.0	25th July 2013	n/a	Initial Document
1.1	30th October 2013	Contents Page	Point 11 – New content element: Document Control
1.1	30th October 2013	Section 5:	Field Type: 'Usage Rules' is now depicted in this section
1.1	30th October 2013	Section 7: Reason Codes	ISO Code: DNOR has been added
1.1	30th October 2013	Section 8 & Section 9	Font used in Fields & Sample File has been changed to Verdana to differentiate 'i' from 'l'
1.1	30th October 2013	Section 8: File Format	'Usage Rules' graphic has been added to the Legend
			1.6: Field / Tag Name: <DbtrAgt> has been changed to <CdtrAgt>
			3.120, 3.121 & 3.129: Data Type: 'ExternalOrganisationIdentification1Code' has been changed to 'ExternalPersonalIdentification1Code'
1.1	30th October 2013	Section 9: PAIN.002.001.03 Sample File	The Doctype has been updated to include the following statement: xmlns:xsd="http://www.w3.org/2001/XMLSchema"
			Sample IBANs & BICs have been updated
1.2	1st December 2015	Section 8: File Format	Pg.19.New Usage Rule to incorporate IBAN only legislation.
1.3	23rd June 2016	Section 7: Reason Codes	Removed Reason Code FF05 as per SEPA DD Rulebook 9,2 Changes
1.3	23rd June 2016	Section 8 & 9 : File Format & PAIN.002.001.03 Sample File	Mapping of PAIN.008 amendment tag changes(as per SEPA DD Rulebook9.2) to PAIN.002 tags 3.79 and 3.80

Disclaimer: This document is for information purposes only and no guarantee or warranty is given in respect of the accuracy or completeness of this document, or its' content, which are subject to change. Bank of Ireland accepts no liability for any losses howsoever arising in reliance on this document or its content.